



## **Prefabricated Strongroom Grade III (LW)**

Robur's Prefabricated strongroom in Grade III (LW) consists of wall, ceiling and floor panels welded or bolted together enabling installation in location where welding is not possible. The Strongroom design is adapted to each project's conditions and needs. The Strongroom is constructed with modular panels for a quick and easy assembly, disassembly and extension. The vault door must have the same burglary protection grade as the panels.



The panels in Grade III (LW) have a primed steel sheet surface on all sides.



Robur's prefabricated strongroom can be fitted with reinforcements blocks for ventilation on special request.



As standard, the strongroom is equipped with a row of 8 conduits with  $\varnothing 18$ , placed above the door. Different placement and number of conduits is possible on special request.



Burglary protection certified by SBSC according to the european standard EN 1143-1.

## WEIGHT AND MEASUREMENTS

	RVV Grade III (LW)
<b>Panels - thickness</b> mm	75
<b>Panels - Weight</b> kg/m <sup>2</sup>	125
<b>Max internal span without beams and pillars</b> mm	3500
<b>Minimum internal width</b> mm	1220
<b>Minimum internal height</b> (At clear height of door: 2000 mm)	2100



We reserve the right to alter the specification without prior notice.



**Head office:**  
Robur Safe AB  
Lundbyvägen 8  
311 68, Slöinge  
Sweden

+ 46 346 260 260  
info@robursafe.com  
www.robursafe.com